0 0 0 0 4 9 0 1 9 3 5

LBL-6884
UC-25
TID-4500-R66

For Reference

Not to be taken from this room

RECEIVED
LAWRENCE
BERKELEY LABORATORY

APR 12 1978

LIBRARY AND
DOCUMENTS SECTION

Energy and Environment Division

Determination Of The Recovery Stresses Developed By Shape Memory Alloys

H. A. Mohamed

March 1978

Lawrence Berkeley Laboratory University of California/Berkeley

Prepared for the U.S. Department of Energy under Contract No. W-7405-ENG-48

LBL-6884

25

LEGAL NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Printed in the United States of America
Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161
Price: Printed Copy, $ 4.00 Domestic; $ 8.00 Foreign
Microfiche, $ 3.00 Domestic; $ 4.50 Foreign

0 0 0 0 4 9 0 1 9 3 6

DETERMINATION OF THE RECOVERY STRESSES DEVELOPED BY SHAPE MEMORY ALLOYS

H. A. MOHAMED

ENERGY AND ENVIRONMENT DIVISION
LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA
BERKELEY, CALIFORNIA 94720

The mechanical shape memory effect is exhibited by several alloys all of which undergo thermoeleastic martensitic transformation [1]. The memory effect is demonstrated by inducing a macroscopic strain within a certain range in a specimen while in martensitic - state and then heating to revert martensite to the high temperature phase (htp). During reversion, the specimen tends to recover its original unstrained shape. Strain recovery starts at the A_s temperature and finishes at the A_f temperature.*

One of the most interesting applications of shape memory alloys is in energy conversion devices that utilize the memory effect in converting low-grade heat sources into useful mechanical work [2 - 4]. In evaluating the performance of a particular alloy in such devices it becomes essential to determine the levels of recovery stresses developed during the martensite $\longrightarrow$ htp transformation upon heating. There have been a few investigations dealing with experimental measurements of the recovery stresses developed by Ni - Ti alloys near the equi-atomic composition [5, 6]. However, no attempt has been made as yet to predict these stresses. In the present paper, a simple relation-

---

*A_s = temperature at which the martensite $\longrightarrow$ htp transformation starts during heating.

A_f = temperature at which this transformation finishes during heating.

**A recovery stress is defined as the external stress required to balance the internal stresses that tend to revert martensite to the htp.

ship has been developed between the recovery stresses, temperature and strain

For the discussions which follow, it is instructive to identify a reference point from which the macroscopic strain is measured i.e., a zero - point strain. This can conveniently be taken to be the point at which the material consists entirely of the htp.

Consider a polycrystalline shape memory alloy that has been almost entirely transformed to martensite by cooling it to a temperature at or below its respective martensite - finish temperature M_f. In the absence of an external and appreciable internal stresses, all the martensite variants that are crystallographically equivalent would form with equal probability. Therefore, no net macroscopic strain as measured from the zero - point would be expected and hence no recovery stresses would develop during the reverse transformation to the htp. In order to realize a recovery stress, the material must acquire a macroscopic strain relative to the zero - point. In terms of the microstructural features, this corresponds to a certain degree of directionality in the distribution of the martensite variants through-out the microstructure. It has been shown experimentally that any strain within the recoverable range is accommodated by re-orientation of a volume fraction of the thermally induced martensite [7 - 10]. This occurs by preferential growth of the most favorably oriented martensite variants. It is then expected that the recovery stress, σ_r, would be proportional to the volume fraction of re-oriented martensite (V_M). This determines the functional dependence of σ_r on strain ε.

Upon heating to within the A_s - A_f temperature range, a certain volume fraction of martensite tends to revert to the htp. The driving force for such reversion arises from the chemical free energy difference between the two respective structures, the elastic strain energy stored in the lattice during the transformation to martensite and energy associated with reversible defects, e.g., twins. As the temperature increases within the range A_s - A_f, the driving force increases and in turn the volume fraction of martensite that tends to revert to the htp (V_{htp}).

0 0 0 3 4 9 0 1 9 3 7

It follows that σ_r increases as V_{htp} increases with temperature. This determines the functional dependence of σ_r on temperature within the range A_s - A_f.

It can be concluded from the above discussion that:

$$\sigma_r \alpha V_{htp} (T) . V_M (\varepsilon) \quad \ldots\ldots\ldots\

variants would be unaffected and others would be affected to different extents depending on their relative orientation. It then follows that V_M would never achieve unity for any finite strain. A relation which gives V_M as a function of ε must then satisfy the following conditions:

$V_M = 0$ for $\varepsilon = 0$, and

V_M increases with ε (as measured from the zero - point) but never achieves unity.

These conditions can be satisfied by an exponential function of the form:

$$V_M = 1 - \exp^{-C\varepsilon} \quad \ldots\ldots\ldots\

0 0 0 0 4 9 0 1 9 3 8

This work was supported by the Conservation and Solar Applications Division of the U.S. Department of Energy through the Energy and Environment Division of the Lawrence Berkeley Laboratory, University of California, Berkeley.

REFERENCES

1) J. Perkins, ed., "Shape Memory Effects in Alloys," (Plenum Press, New York, 1975).

2) R. Banks, Naturwissenschaften, 62 (1975) 305.

3) R. Banks, in "Shape Memory Effects in Alloys," (Plenum Press, New York, 1975) p. 537.

4) R. Banks and M. Wahlig, Presented at the International Solar Energy Society Meeting, Winnipeg, Canada, Aug. 1976, Lawrence Berkeley Laboratory Report No. 5293.

5) G. R. Edwards, J. Perkins and J. M. Johnson, Scripta Met. 11 (1975) 1167.

6) W. B. Cross, A. H. Karigits and F. J. Stimler, "Nitinol Characterization Study," NASA Contractor Report (1969) Cr - 1433.

7) H. A. Mohamed and J. Washburn, J. Mater. Scien. 12 (1977) 469.

8) H. A. Mohamed and J. Washburn, Met. Trans. 7A (1976) 1042.

9) C. M. Wayman, in "Shape Memory Effects in Alloys" (Plenum Press, New York, 1975) p. 1.

10) L. Delaey, R. V. Krishnan, H. Tas and H. Warlimont, J. Mater. Scien. 9 (1974) 1521.

11) J. Burke, "The Kinetics of Phase Transformations in Metals" (Pergamon Press, 1965) p. 45.

This report was done with support from the United States Energy Research and Development Administration. Any conclusions or opinions expressed in this report represent solely those of the author(s) and not necessarily those of The Regents of the University of California, the Lawrence Berkeley Laboratory or the United States Energy Research and Development Administration.

0 0 0 0 4 5 0 2 2 9 4